

# EARTH DRILL SPECIFICATION



	TORQUE RANGE (Nm)	OIL PRESSURE RANGE (Bar)	OIL FLOW RANGE (lpm)	UNIT HEIGHT (mm)	UNIT WEIGHT (kg)
1200	189 - 1164	30 - 185	15 - 32	450	35
X1500	511 - 1496	70 - 205	20 - 45	585	46
X2000	639 - 2190	70 - 240	25 - 57	585	47
X2500	830 - 2847	70 - 240	27 - 65	585	48
3000MAX	959 - 2877	80 - 240	27 - 75	665	71
3500MAX	1205 - 3614	80 - 240	40 - 85	665	73
4500MAX	1500 - 4499	80 - 240	50 - 95	665	75
ML1500	511 - 1496	70 - 205	20 - 45	406	38
ML2000	639 - 2190	70 - 240	25 - 57	465	40
ML2500	830 - 2847	70 - 240	27 - 65	465	40
3000TC	959 - 3119	80 - 260	5 - 35	665	73
5500TC	1685 - 5477	80 - 260	15 - 50	780	108
7000TC	2098 - 6819	80 - 260	15 - 50	780	110
5500MAX	1685 - 5477	80 - 260	40 - 115	780	108
7000MAX	2133 - 6931	80 - 260	60 - 135	780	112
8000MAX	2717 - 8152	80 - 240	70 - 150	780	116
10000	3281 - 10662	80 - 260	70 - 150	883	162
12000MAX	3998 - 11995	80 - 240	80 - 170	930	172
15000MAX	5024 - 15071	80 - 240	80 - 170	930	173
20000MAX	13043 - 19564	160 - 240	80 - 170	1130	268
25000MAX	16503 - 24755	160 - 240	80 - 170	1130	269
35000MAX	20510 - 35323	180 - 310	80 - 225	1411	442
42000MAX	24612 - 42387	180 - 310	80 - 225	1411	442
50000MAX	23758 - 47515	160 - 320	100 - 280	1411	472